



İMAJ TEKNİK
ELEKTRİK ELEKTRONİK MALZ. SAN. VE TİC. LTD. ŞTİ.

Ordering code: Contactor for battery voltages



Example: **C137 C/ 24EV-V1 001**

Series	C137	Special design	001	Made for customer ...
Contact type	C NO	Type and # of auxiliary contact*	V	Microswitch
Coil voltage	12 12 V DC 60 60 V DC 24 24 V DC 72 72 V DC 34 34 V DC 96 96 V DC 36 36 V DC 110 110 V DC 48 48 V DC 120 120 V DC	Coil suppression	1	Number of
		Coil tolerance	V	Varistor
			E	-30% ... +25% U _n

* Microswitch (to be ordered separately), 1 switch max. possible

Type C contactors are NO contactors fitted with magnetic blowout. Here the NO contact functions as circuit-breaker within an open contact design. Type H contactors, however, feature an additional NC contact which is galvanically isolated and has a potential of its own. **So, for type H SPDT contactors is to be observed that only the NO contact may be used for breaking the circuit, whereas the NC contact should only be used for power transmission functions.**



Emekyemez Mah. Yüksek Minare Sk. No:8 / 17
80020 Karaköy / İstanbul
Tel:212/2359535
Fax:212/2359537