



İMAJ TEKNİK
ELEKTRİK ELEKTRONİK MALZ. SAN. VE TİC. LTD. ŞTİ.

Ordering code: Contactor for battery voltages



Example: **C195 S/ 24EV-U2 001**

Series	C195	Special design	001	Made for customer ...
Contact type	S NC	Type and # of auxiliary contact*	U	S870 silver-plated
Coil voltage	24	24 V DC	72	72 V DC
	36	36 V DC	80	80 V DC
	48	48 V DC	96	96 V DC
	60	60 V DC	110	110 V DC
		Coil suppression	V	Varistor
		Coil tolerance	E	-30% ... +25% U _n

* Microswitch (to be ordered separately), 2 switches max. possible

Type S contactors are DC NO contactors fitted with magnetic blowout. Here the NO contact functions as circuit-breaker with high breaking capacity in an enclosed space.

Type W contactors, however, feature an additional NC contact which is galvanically isolated and has a potential of its own. **So, for type W SPDT contactors is to be observed that the NO contact is designed for breaking the circuit. The NC contact, in contrast, is designed for carrying lesser loads.**



adresimiz değişti
Emekyemez Mah. Yüksek Minare Sk. No:8 / 17
80020 Karaköy / İstanbul
Tel:212/2359535
Fax:212/2359537