



İMAJ TEKNİK
ELEKTRİK ELEKTRONİK MALZ. SAN. VE TİC. LTD. ŞTİ.

Ordering code: Contactor for battery voltages



Example: **C195 W/ 24EV-U2 001**

Series	C195	Special design	001	Made for customer ...
Contact type	W NO + NC	Type and # of auxiliary contact*	U	S870 silver-plated
Coil voltage	11 11 V DC 24 24 V DC 30 30 V DC 36 36 V DC 72 72 V DC 96 96 V DC	J	S870 gold-plated	
		2	Number of	
		Coil suppression	V	Varistor
		Coil tolerance	E	-30% ... +25% U _n

* Microswitch (to be ordered separately), 2 switches max. possible

Type S contactors are DC NO contactors fitted with magnetic blowout. Here the NO contact functions as circuit-breaker with high breaking capacity in an enclosed space.

Type W contactors, however, feature an additional NC contact which is galvanically isolated and has a potential of its own. **So, for type W SPDT contactors is to be observed that the NO contact is designed for breaking the circuit. The NC contact, in contrast, is designed for carrying lesser loads.**



**adresimiz
değiştii** Emekyemez Mah.Yüksek Minare Sk. No:8 / 17
80020 Karaköy / İstanbul
Tel:212/2359535
Fax:212/2359537